

Viewtech High Quality IP CCTV

Dahuatech 2MP IR Vandal Dome

2MP, 3-9mm Motorised lens with Autofocus, IR, PoE, SD Card




Features

- 1/3" 2Megapixel progressive scan Exmor CMOS
- H.264 & MJPEG dual-stream encoding
- 25/30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3~9mm varifocal motorized lens (3202)
- Built-in 2/1 alarm in/out
- Max. IR LEDs length 20m
- Micro SD memory slot for onboard recording
- IP66 Water rating
- IK10 Endurance rating
- PoE (power over ethernet enabled)
- Comes with free PSS recording software for PC based recording
- Fully Detailed Android & iPhone application available (search gDMSS)
- Easy to use web based interface
- Easy to use config tool which will find the camera when connected to any network



PSS Software



Mobile Phone App Screen Shots



Technical Specifications

Model	IPC-HDBW3200P	IPC-HDBW3202P	IPC-HDBW3200N	IPC-HDBW3202N
Camera				
Image Sensor	1/3" 2Megapixel Exmor CMOS			
Effective Pixels	1920(H)x1080(V)			
Scanning System	Progressive			
Electronic Shutter Speed	Auto/Manual 1/3~1/10000		Auto/Manual 1/4~1/10000	
Min. Illumination	Color: 0.1Lux/F1.2, B/W: 0.01Lux/F1.2; 0Lux/F1.2(IR on)			
S/N Ratio	> 50dB			
Video Output	1 channel, BNC(1.0Vp-p/75Ω)			
Camera Features				
Max. IR LEDs Length	20m			
Day/Night	Auto(ICR)/Color/B/W			
Backlight Compensation	BLC / HLC / DWDR			
White Balance	Auto			
Gain Control	Auto/Manual			
Noise Reduction	2D			
Privacy Masking	Up to 4 areas			
Lens				
Focal Length	3.3-12mm	3-9mm motorized	3.3-12mm	3-9mm motorized
Max Aperture	F1.4	F1.2	F1.4	F1.2
Focus Control	Manual	Auto	Manual	Auto
Angle of View	H: 79.3°(Wide)~ 29.8°(Tele)	H: 105°(Wide)~ 36°(Tele)	H: 79.3°(Wide)~ 29.8°(Tele)	H: 105°(Wide)~ 36°(Tele)
Lens Type	Manual / Auto Iris (DC)	Motorized / Auto Iris(DC)	Manual / Auto Iris (DC)	Motorized / Auto Iris(DC)
Mount Type	Board-in Type			
Video				
Compression	H.264 / MJPEG			
Resolution	1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)		1080P(1920×1080) / 720P(1280×720) / D1(704×480) / CIF(352×240)	
Frame Rate	Main Stream	1080P/720P(1 ~ 25/30fps)		
	Sub Stream	D1/CIF(1 ~ 25/30fps)		
Bit Rate	H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps			
Audio				
Compression	G.711a / G.711u (64kbps) / PCM(128kbps)			
Interface	1/1 channel In/Out			
Network				
Ethernet	RJ-45 (10/100Base-T)			
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP,			
	NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour			
ONVIF	ONVIF Ver. 2.2 Profile S			
Max. User Access	10 users			
Smart Phone	iPhone, iPad, Android, Windows Phone			
Auxiliary Interface				
Memory Slot	Micro SD, Max 32GB			
Alarm	1/1 channel In/Out			
General				
Power Supply	DC12V/AC24V, PoE(802.3af)			
Power Consumption	<10W			
Working Environment	-10°C~+60°C, 10%~90%			
Protection Level	IK10 & IP66			
Dimensions	Φ151mm×119mm			
Weight	1.1kg			

Distributed in NZ by



www.viewtech.co.nz, 0800 888 324

Manufactured by

